

ONE

With its durable die-cast chassis, Kenwood's ProTalk® meets military standards for reliable performance in demanding work environments.

The aluminium die-cast chassis provides exceptional strength. This combines with a sealed case design to ensure that the ProTalk® will provide years of reliable use. In addition to hard knock and drops, this rugged radio is also built to survive all weather environments. In fact, it satisfies or exceeds the stringent IP54/55 dust and water intrusion standards and also the US MIL-STD 810 C. D. E & F environmental standards, including the demanding "blowing rain" test.

| MIL-STD | Method / Procedures | | | |
|-------------------|----------------------|---------------------|---------------------|--------------------|
| | 810C | 810D | 810E | 810F |
| Low Pressure | 500.1/Proc. I | 500.2/Proc. I, II | 500.3/Proc. I, II | 500.4/Proc. I, II |
| High Temperature | 501.1/Proc. I, II | 501.2/Proc. I, II | 501.3/Proc. I, II | 501.4/Proc. I, II |
| Low Temperature | 502.1/Proc. I | 502.2/Proc. I, II | 502.3/Proc. I, II | 502.4/Proc. I, II |
| Temperature Shock | 503.1/Proc. I | 503.2/Proc. I | 503.3/Proc. I | 503.4/Proc. I, II |
| Solar Radiation | 505.1/Proc. I | 505.2/Proc. I | 505.3/Proc. I | 505.4/Proc. I |
| Rain | 506.1/Proc. I, II | 506.2/Proc. I, II | 506.3/Proc. I, II | 506.4/Proc. I, III |
| Humidity | 507.1/Proc. I, II | 507.2/Proc. II, III | 507.3/Proc. II, III | 507.4 |
| Salt Fog | 509.1/Proc. I | 509.2/Proc. I | 509.3/Proc. I | 509.4 |
| Dust | 510.1/Proc. I | 510.2/Proc. I | 510.3/Proc. I | 510.4/Proc. I, III |
| Vibration | 514.2/Proc. VIII, X | 514.3/Proc. I | 514.4/Proc. I | 514.5/Proc. I |
| Shock | 516.2/Proc. I, II, V | 516.3/Proc. I, IV | 516.4/Proc. I, IV | 516.5/Proc. I, IV |

Optional Accessories

KNB-29N

Ni-MH Battery. 16 hours (7.2V, 1500mAh)

KNB-30A

Ni-Cd Battery.

KNB-45L

Li-ion Battery,

(7.4V, 2000mAh)

20 hours

KSC-31

KSC-35

Rapid Charger

for the KNB-45L

KMC-17

Speaker Microphone

Rapid Charger

for the KNB-29N and KNB-30A

11 hours (7.2V, 1100mAh)





KHS-1

Headset

with VOX/F

KHS-7

Single-Mut

KHS-8BL

2-Wire Palm

Microphone

KHS-9BL 3-Wire Lapel

Microphone with

Earphone (Black)

KHS-10-0H

Noise-Reduction

Headset with Noise-Cancelling

Microphone

(Black)

Headset





























Not all accessories and options may be available in all markets. Contact an authorized Kenwood dealer for details.

Specifications

- Number of channels: 16
- RF output power: 0.5W ERP
- Dimensions (W x H x D): 54 x 122 x 32mm including battery
- Weight: 280g with KNB-45L battery

Kenwood follows a policy of continuous advancement in development. For this reason, specifications may be changed without notice. ProTalk® is a registered trademark of Kenwood Corporation.

Listen to the Future

Now we want to expand the world of sound in ways that only Kenwood can, listening to our customers and to the pulse of the coming age as we head toward a future of shared discovery, inspiration and enjoyment



Kenwood Electronics U.K. Ltd.

Kenwood House, Dwight Road, Watford, Herts, WD18 9EB, United Kingdom



ProTalk® PMR446 TRANSCEIVER













For Restaurants and Hotels

For Retailers


For Construction

■ 16 Channels

The ProTalk® offers 16 channels, each of which can be programmed by the user to any of the 8 pre-stored frequencies, quided by the voice synthesizer.

■ Versatile Signalling

Sub-audible QT tone & DQT digital codes mute undesired voice traffic audio and segregate user talk groups on shared frequencies or radio systems. Similarly guided by the voice synthesizer, the user can pick any of the pre-stored settings – 26 QT tones and 12 DQT codes (plus Off).



■ Compatibility

Thanks to the pre-stored 8 frequencies and 38 QT tones and DQT codes, the ProTalk® can operate on the same channels and coded squelch tones as other business radio brands. So choosing the rugged Kenwood ProTalk® will not impact on any of your previous investments in radio equipment.

■ All-in-one Package

The ProTalk® is ready for use immediately after purchase. It comes with all necessary accessories, including a rapid charger and a powerful Li-ion battery pack with extra capacity (2000mAh). A handy belt clip is also provided.

■ Long Battery Life

The supplied battery KNB-45L offers up to 20 hours of operation.

■ Talk Range of 5km (3 miles)

The ProTalk® offers 0.5W of power to enable direct radio-toradio communication on the same frequency (simplex) for distances of up to 5km*.

* Talk range will vary depending on terrain, obstructions, and other conditions.

■ Enhanced 2-Way Audio

A portable radio may well have to perform in a noisy environment, so the frequency curve of the ProTalk® has been custom-tuned to optimize two-way communications. Moreover, the 32mm-diameter speaker delivers up to 500mW, ensuring communications are always loud and clear.

Other Features

- Scan Channel Confirmation Mode Key Lock
- Voice Inversion Scrambler Calling Alert
- Time Out Timer Low Battery Warning

Included Accessories

- Li-ion Battery Pack (20 hours) Spring-action Belt Clip
- Rapid Charger

Compact and Lightweight Design, Friendly Controls

The ProTalk® is worthy of an industrial design award – superbly functional and rugged, yet smart enough to look at home in a hotel foyer or restaurant. Every detail has been carefully designed. Its rounded ergonomic contours provide a comfortable hold, while a non-slip elastomer rotary switch ensures a good grip for accurate channel selection.

